



1	Luik
2	Deksel
3	Afdichting boven
4	Afdichting onder
5	Inbusbout

6	Afdekkapje
7	Bodemplaat
8	Wapening
9	Moer
10	Gietdeel aluminium

Vloerluik BVA-SL

Type	Schachtafmeting C x D (mm)	Buitenafmeting A x B (mm)	Inhouwhoogte H (mm)	Gewicht (kg)
BVA-SL 22	200 x 200	290 x 290	ca.50	2
BVA-SL 33	300 x 300	390 x 390	ca.50	3
BVA-SL 44	400 x 400	490 x 490	ca.50	4
BVA-SL 45	450 x 450	540 x 540	ca.50	5
BVA-SL 55	500 x 500	590 x 590	ca.50	6
BVA-SL 64	600 x 400	690 x 490	ca.50	6
BVA-SL 66	600 x 600	690 x 690	ca.50	7
BVA-SL 635	635 x 635	725 x 725	ca.50	8
BVA-SL 77	700 x 700	790 x 790	ca.50	9
BVA-SL 86	800 x 600	890 x 690	ca.50	9
BVA-SL 88	800 x 800	890 x 890	ca.50	10
BVA-SL 105	1000 x 600	1090 x 690	ca.50	10
BVA-SL 108	1000 x 800	1090 x 890	ca.50	12
BVA-SL 110	1000 x 1000	1090 x 1090	ca.50	14



Storax BV
Wattstraat 1
3335 LV Zwijndrecht
Nederland

Tel. : +31 (0)78 303 09 00
Fax : +31 (0)78 610 04 95
E-mail: storax@storax.nl
Website: www.storax.nl

Productgroep : Vloerluik

Onderdeel : Doosnede type BVA-SL

Materiaal : Aluminium

Schaal : 1:2.5

Datum : 20-05-2024

Blad:

BVA-SL DSN